iLIVE 2 HANDHELD

Antenna diversity wireless microphone system

iLive 2 Handheld Antenna Diversity Wireless Microphone System. This system offers 32 selectable channels with automatic channel targeting and synchronization for reliable, interference-free audio. Included are a receiver, handheld transmitter, and jack-to-jack cable. The transmitter features an advanced PCB inside a rugged metal body and uses a dynamic cardioid microphone capsule, suitable for both live stage and conference room applications.

Technical Specifications	iLIVE 2 wireless receiver
Power supply	12-15 V DC, 1.25 A
Output	Balanced XLR, unbalanced 6,3 mm TRS JACK
Receiver way	Two frequency conversion super-heterodynes
Intermediate frequency	10.7 MHz
Antenna	BNC
THD	< 0.7 %
Sensitivity	6 dB µV
Image rejection	36 dB
Max. audio output	0 dB
Dimensions	45 mm x 210 mm x 206mm
Weight	1.3 kg
Material	Steel enclosure, aluminum front panel

iLIVE 2 Handheld Transmitter

iLIVE 2 UHF HANDHELD MICROPHONE WIRELESS TRANSMITTER

The iLive 2 handheld wireless microphone transmitter is designed for use with the iLive 2 wireless microphone system. It features automatic channel synchronization and frequency selection for hassle-free operation. Built with an advanced PCB and a durable metal body, the transmitter includes a dynamic cardioid microphone capsule, making it ideal for versatile applications on stage and in conference rooms.

Technical Specifications	iLIVE 2 Hand Mic
Carrier frequency range	606 MHz - 621 MHz
Modulation	FM
Channels	32
Frequency response	45 Hz - 18 KHz
S/N ratio	> 105 dB
Antenna	Built-in spiral antenna
Transmitter power	3 mW
Working range	90 m (Note: actual range depends on RF signal absorption, reflection and interference)
Polar pattern	Cardioid
Battery	2 x 1,5 V AA Alkaline battery
Dimensions	240 mm (length)
Weight	302 g