

iLIVE 2 LAVALIER

Antenna diversity wireless microphone system

The iLive 2 lavalier antenna diversity wireless microphone system offers 32 selectable channels with automatic channel targeting and synchronization. Each set includes a microphone signal receiver, bodypack transmitter, lavalier condenser microphone, and jack-to-jack cable. The system delivers highly stable RF transmission and reception, with selectable frequency channels to ensure interference-free operation across diverse environments.



Technical Specifications	iLIVE 2 wireless receiver
Power supply	12-15 V DC, 1.25 A
Output	Balanced XLR, unbalanced 6,3 mm TRS JACK
Receiver way	Two frequency conversion super-heterodynes
Intermediate frequency	10.7 MHz
Antenna	BNC
THD	< 0.7 %
Sensitivity	6 dB μ V
Image rejection	36 dB
Max. audio output	0 dB
Dimensions	45 mm x 210 mm x 206mm
Weight	1.3 kg
Material	Steel enclosure, aluminum front panel

iLIVE 2BP

iLIVE 2 UHF BODY PACK WIRELESS TRANSMITTER

The iLive 2 BP is a bodypack wireless transmitter featuring an integrated LCD display that provides real-time channel frequency and battery level monitoring. Designed for seamless compatibility with iLive 2 receiver systems, it ensures reliable wireless transmission with user-friendly status feedback for professional audio applications.



Technical Specifications	iLIVE 2BP
Carrier frequency range	606 MHz - 621 MHz
Modulation	FM
Channels	32
Frequency response	45 Hz - 18 KHz
S/N ratio	> 105 dB
Antenna	1/4 wave antenna
Transmitter power	3 mW
Working range	60 m (Note: actual range depends on RF signal absorption, reflection and interference)
Battery	2 x 1,5 V AA alkaline battery
Dimensions	110 mm x 64 mm x 25 mm
Weight	76 g
Material	Plastic

iLIVE 12LM

MICROPHONE FOR iLIVE 1 & iLIVE 2 BODY PACK TRANSMITTERS

Designed for professional use in TV and radio studios as well as conference applications, the iLive 12LM lavalier microphones deliver clear and natural sound reproduction. For wireless operation, they require connection to an iLive 1 or iLive 2 bodypack transmitter. Ideal for scenarios demanding discreet, hands-free audio capture.



Technical Specifications	iLIVE 12LM
Capsule type	Condenser
Impedance	200 Ω
Sensitivity	-46 dB
Frequency response	50 Hz - 18 kHz
Connector	4-pin mini XLR
Phantom power voltage	5 V DC
Cable length	1 m
Weight	21 g
Colour	Black
Accessories	Windscreen